



Daylight Savings LLC Product List

Advantages:

- ◆ UL/CUL(E352762), DLC listed, SAA approved
- ◆ High quality CREE chips, Mean Well UL/CUL driver
- ◆ Voltage options: AC100-277V, 347~480V
- ◆ Warranty period: 5 years
- ◆ Multiple use- IP65 rating, for indoor&outdoor use: highbays, flood lights, spotlights, high poles, stadium lights...
- ◆ Excellent heat sink with Copper heat pipe
- ◆ IP65: suitable for wet/damp/dry locations
- ◆ E-PTFE waterproof breathable membrane
- ◆ Powers: 75/100/120/150/200/300/400/450W

Multi-purpose Indoor / Outdoor LED High Bays / Flood Lights (UL/CUL: E352762, DLC Listing)

Product list including below items:

DL-FLHB10	100W	100-277V	cULus/SAA
DL-FLHB11	120W	100-277V	cULus/SAA
DL-FLHB15	150W	100-277V	DLC/cULus/SAA
DL-FLHB16	200W	100-277V	DLC/cULus/SAA
DL-FLHB17	300W	100-277V	cULus/SAA
DL-FLHB18	400W	100-277V	cULus/SAA
DL-FLHB14	465W	100-277V	DLC/cULus/SAA
DL-FLHB06-HV	75W	347/480V	DLC/cULus
DL-FLHB10-HV	100W	347/480V	DLC/cULus/SAA
DL-FLHB15-HV	150W	347/480V	DLC/cULus/SAA
DL-FLHB16-HV	200W	347/480V	cULus/SAA
DL-FLHB13-HV	450W	347/480V	cULus/SAA





100-277V Series

100W



Model No.	DL-FLHB10
Input Voltage:	AC100-277V (50~60Hz)
Input Power:	LED: 100W Total: 103W
Luminous Flux:	9,200 LM
LED Source:	High power CREE LEDs
Color Temp.:	3000K /4100K /5500K /6000K
View Angle:	25° / 60° / 90°
Fixture Material:	Diecast aluminum+Copper Pipe+Glass
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762)
Internal Driver:	LM79/LM80/IES available
Fixture info.:	14.7" (L)*14.7"(W)*16.1"(H), 14.2kg

Spec.



Spec.

Model No.	DL-FLHB11
Input Voltage:	AC100-277V (50~60Hz)
Input Power:	LED: 120W Total: 125W
Luminous Flux:	11,040 LM
LED Source:	High power CREE LEDs
Color Temp.:	3000K /4100K /5500K /6000K
View Angle:	25° / 60° / 90°
Fixture Material:	Diecast aluminum+Copper Pipe+Glass
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762)
Internal Driver:	LM79/LM80/IES available
Fixture info.:	14.7" (L)*14.7"(W)*16.1"(H), 14.3kg

120W



Spec.

150W



Model No.	DL-FLHB15-DLC
Input Voltage:	AC100-277V (50~60Hz)
Input Power:	LED: 150W Total: 155W
Luminous Flux:	13,100 LM
LED Source:	High power CREE LEDs
Color Temp.:	3000K /4100K /5500K /6000K
View Angle:	25° / 60° / 90°
Fixture Material:	Diecast aluminum+Copper Pipe+Glass
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762)
Internal Driver:	LM79/LM80/IES available
Fixture info.:	14.7" (L)*14.7"(W)*16.1"(H), 14.4kg



Spec.

Model No.	DL-FLHB16-DLC
Input Voltage:	AC100-277V (50~60Hz)
Input Power:	LED: 200W Total: 205W
Luminous Flux:	17,500 LM
LED Source:	High power CREE LEDs
Color Temp.:	3000K /4100K /5500K /6000K
View Angle:	25° / 60° / 90°
Fixture Material:	Diecast aluminum+Copper Pipe+Glass
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762)
Internal Driver:	LM79/LM80/IES available
Fixture info.:	14.7" (L)*14.7"(W)*16.1"(H), 14.6kg

200W



300W



Spec.

Model No.	DL-FLHB17
Input Voltage:	AC100-277V (50~60Hz)
Input Power:	LED: 300W Total: 305W
Luminous Flux:	27,600 LM
LED Source:	High power CREE LEDs
Color Temp.:	3000K /4100K /5500K /6000K
View Angle:	25° / 60° / 90°
Fixture Material:	Diecast aluminum+Copper Pipe+Glass
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762)
Internal Driver:	LM79/LM80/IES available
Fixture info.:	14.7" (L)*14.7"(W)*16.1"(H), 14.8kg



Spec.

Model No.	DL-FLHB18
Input Voltage:	AC100-277V (50~60Hz)
Input Power:	LED: 400W Total: 405W
Luminous Flux:	36,800 LM
LED Source:	High power CREE LEDs
Color Temp.:	3000K /4100K /5500K /6000K
View Angle:	25° / 60° / 90°
Fixture Material:	Diecast aluminum+Copper Pipe+Glass
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762)
Internal Driver:	LM79/LM80/IES available
Fixture info.:	14.9" (L)*14.2"(W)*17.6"(H), 15 kg

400W





465W



Spec.

Model No.	DL-FLHB14
Input Voltage:	AC100-277V (50~60Hz)
Input Power:	LED: 465W Total: 480W
Luminous Flux:	41,850 LM
LED Source:	High power CREE LEDs
Color Temp.:	3000K /4100K /5500K /6000K
View Angle:	25° / 60° / 90°
Fixture Material:	Diecast aluminum+Copper Pipe+Glass
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762), DLC (pending)
Internal Driver:	LM79/LM80/IES available
Fixture info.:	14.9" (L)*14.2"(W)*17.6"(H), 15 kg



347-480V Series

75W



Spec.

Model No.	DL-FLHB06-HV
Input Voltage:	AC347-480V (50~60Hz)
Input Power:	LED:73W Total: 75W
Luminous Flux:	6,600 LM
LED Source:	High power CREE LEDs
Color Temp.:	3000K /4100K /5500K /6000K
View Angle:	25° / 60° / 90°
Fixture Material:	Diecast aluminum+Copper Pipe+Glass
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762)
Internal Driver:	LM79/LM80/IES available
Fixture info.:	14.7" (L)*14.7"(W)*16.1"(H), 14.3kg



Spec.

Model No.	DL-FLHB10-HV
Input Voltage:	AC347-480V (50-60Hz)
Input Power:	LED: 100W Total: 103W
Luminous Flux:	9,150 LM
LED Source:	High power CREE LEDs
Color Temp.:	3000K /4100K /5500K /6000K
View Angle:	25° / 60° / 90°
Fixture Material:	Diecast aluminum+Copper Pipe+Glass
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762)
Internal Driver:	LM79/LM80/IES available
Fixture info.:	14.7" (L)*14.7"(W)*16.1"(H), 14.3kg

100W



Spec.

150W



Model No.	DL-FLHB15-HV
Input Voltage:	AC347-480V (50-60Hz)
Input Power:	LED: 150W Total: 155W
Luminous Flux:	13,650 LM
LED Source:	High power CREE LEDs
Color Temp.:	3000K /4100K /5500K /6000K
View Angle:	25° / 60° / 90°
Fixture Material:	Diecast aluminum+Copper Pipe+Glass
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762)
Internal Driver:	LM79/LM80/IES available
Fixture info.:	14.7" (L)*14.7"(W)*16.1"(H), 14.5kg



Spec.

Model No.	DL-FLHB16-HV
Input Voltage:	AC347-480V (50~60Hz)
Input Power:	LED: 200W Total: 205W
Luminous Flux:	18,200 LM
LED Source:	High power CREE LEDs
Color Temp.:	3000K /4100K /5500K /6000K
View Angle:	25° / 60° / 90°
Fixture Material:	Diecast aluminum+Copper Pipe+Glass
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762)
Internal Driver:	LM79/LM80/IES available
Fixture info.:	14.7" (L)*14.7"(W)*16.1"(H), 14.9kg

200W



Spec.

450W



Model No.	DL-FLHB13-HV
Input Voltage:	AC347-480V (50~60Hz)
Input Power:	LED: 450W Total: 465W
Luminous Flux:	42,596 LM
LED Source:	High power CREE LEDs
Color Temp.:	3000K /4100K /5500K /6000K
View Angle:	25° / 60° / 90°
Fixture Material:	Diecast aluminum+Copper Pipe+Glass
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762), DLC
Internal Driver:	LM79/LM80/IES available
Fixture info.:	14.9" (L)*14.2"(W)*17.6"(H), 16 kg

