

## Daylight Savings LLC Product List

### Advantages:

- ◆ UL/CUL(E352762)
- ◆ High quality CREE chips
- ◆ Mean Well UL/CUL driver
- ◆ Best quality with 5-Year Warranty
- ◆ Universal voltage: 100-277V/347V/480V
- ◆ Heat and Shock Resistant
- ◆ Available with sensor
- ◆ Positive cooling technology with fan
- ◆ Precision die cast aluminum housing
- ◆ Protective powder coating for lasting appearance

### Wall Pack Fixtures Series

#### Product list including below items:

DL-WP01	20W	100-277V	DLC/cULus/CE/RoHS
DL-WP02	25W	100-277V	DLC/cULus/CE/RoHS
DL-WP04	43W	100-277V	DLC/cULus/CE/RoHS
DL-WP06	75W	100-277V	DLC/cULus/CE/RoHS
DL-WP09	90W	100-277V	DLC/cULus/CE/RoHS
DL-WP11	120W	100-277V	DLC/cULus/CE/RoHS
DL-WPF04	43W	100-277V	cULus
DL-WPF06	75W	100-277V	cULus
DL-WPF09	90W	100-277V	cULus
DL-WPF11	120W	100-277V	cULus



**STANDARD LED WALL PACKS <1 >**

(UL/CUL: E352762, DLC Listed, suitable for wet location)

**Spec.**

Model No.	DL-WP01 (For 70W MH/HPS)
Input Voltage:	AC100-277V
Input Power:	LED: 18W   Total: 20W
Luminous Flux:	1,650 LM
LED Source:	CREE LED chips
Color Temp.:	3000K/4100K/5500K/6000K
View Angle:	120 degree
Fixture Material:	Die-cast aluminum + PC lens
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762), CE&ROHS
Test Reports:	LM79/LM80/IES available
Fixture info.:	10.8"L x 6.7"W x 5.1"H, 2.8kg



**20W**



**25W**



**Spec.**

Model No.	DL-WP02 (For 70W MH/HPS)
Input Voltage:	AC100-277V
Input Power:	LED: 25W   Total: 28W
Luminous Flux:	2,380 LM
LED Source:	CREE LED chips
Color Temp.:	3000K/4100K/5500K(DLC)/6000K
View Angle:	120 degree
Fixture Material:	Die-cast aluminum + Glass lens
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762)
Test Reports:	LM79/LM80/IES available
Fixture info.:	12.9"L x 7.8"W x 5.5"H, 3.8 kg

**STANDARD LED WALL PACKS**

< 2 >

Spec.

<b>Model No.</b>	<b>DL-WP04 (For 150W MH/HPS)</b>
Input Voltage:	AC100-277V
Input Power:	LED: 40W   Total: 43W
Luminous Flux:	3,655 LM
LED Source:	CREE LED chips
Color Temp.:	3000K/4100K(DLC)/5500K(DLC)/6000K
View Angle:	120 degree
Fixture Material:	Die-cast aluminum + Glass lens
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762)
Test Reports:	LM79/LM80/IES available
Fixture info.:	13.1"L x 9.5"W x 7.5"H, 5.5 kg



**43W**



Spec.

<b>Model No.</b>	<b>DL-WP06 (For 250W MH/HPS)</b>
Input Voltage:	AC100-277V (347-480V available)
Input Power:	LED: 73W   Total: 75W
Luminous Flux:	6,375 LM
LED Source:	CREE LED chips
Color Temp.:	3000K/4100K(DLC)/5500K(DLC)/6000K
View Angle:	120 degree
Fixture Material:	Die-cast aluminum + Glass lens
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762)
Test Reports:	LM79/LM80/IES available
Fixture info.:	13.1"L x 9.5"W x 7.5"H, 5.8 kg



**75W**



**STANDARD LED WALL PACKS**

< 3 >

Spec.

<b>Model No.</b>	<b>DL-WP09 (For 320W MH/HPS)</b>
Input Voltage:	AC100-277V
Input Power:	LED: 90W   Total: 95W
Luminous Flux:	7,400 LM
LED Source:	CREE LED chips
Color Temp.:	3000K/4100K(DLC)/5500K(DLC)/€
View Angle:	120 degree
Fixture Material:	Die-cast aluminum + Glass lens
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762)
Test Reports:	LM79/LM80/IES available
Fixture info.:	16.9"L x 9.4" W x 9.3"H, 6.5 kg



**90W**



Spec.

<b>Model No.</b>	<b>DL-WP11 (For 400W MH/HPS)</b>
Input Voltage:	AC100-277V (347-480V available)
Input Power:	LED: 120W   Total: 125W
Luminous Flux:	10,200 LM
LED Source:	CREE LED chips
Color Temp.:	3000K/4100K(DLC)/5500K(DLC)/6000K
View Angle:	120 degree
Fixture Material:	Die-cast aluminum + Glass lens
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762)
Test Reports:	LM79/LM80/IES available
Fixture info.:	16.9"L x 9.5"W x 12.7"H, 8.8 kg



**FULL CUT OFF LED WALL PACKS (UL/CUL: E352762, suitable for wet location) < 1 >**

Spec.

Model No.	DL-WPF04 (For 150W MH/HPS)
Input Voltage:	AC100-277V
Input Power:	LED: 40W   Total: 43W
Luminous Flux:	3,655 LM
LED Source:	CREE LED chips
Color Temp.:	3000K/4100K/5500K/6000K
View Angle:	120 degree
Fixture Material:	Die-cast aluminum + Glass lens
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762)
Test Reports:	LM79/LM80/IES available
Fixture info.:	13.1"Lx 9.5"W x 11.5"H, 6.5 kg

**43W**



Spec.

Model No.	DL-WPF06 (For 250W MH/HPS)
Input Voltage:	AC100-277V (347-480V available)
Input Power:	LED: 73W   Total: 75W
Luminous Flux:	6,375 LM
LED Source:	CREE LED chips
Color Temp.:	3000K/4100K/5500K/6000K
View Angle:	120 degree
Fixture Material:	Die-cast aluminum + Glass lens
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762)
Test Reports:	LM79/LM80/IES available
Fixture info.:	13.1"Lx 9.5"W x 11.5"H, 6.8kg



**75W**



**FULL CUT OFF LED WALL PACKS (UL/CUL: E352762, suitable for wet location) < 2 >**

Spec.

<b>Model No.</b>	<b>DL-WPF09 (For 320W MH/HPS)</b>
Input Voltage:	AC100-277V
Input Power:	LED: 90W   Total: 95W
Luminous Flux:	7,400 LM
LED Source:	CREE LED chips
Color Temp.:	3000K/4100K/5500K/6000K
View Angle:	120 degree
Fixture Material:	Die-cast aluminum + Glass lens
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762)
Test Reports:	LM79/LM80/IES available
Fixture info.:	13.1"Lx 9.5"W x 11.5"H,7.0kg

**90W**



**120W**



Spec.

<b>Model No.</b>	<b>DL-WPF11 (For 400W MH/HPS)</b>
Input Voltage:	AC100-277V (347-480V available)
Input Power:	LED: 120W   Total: 125W
Luminous Flux:	10,200 LM
LED Source:	CREE LED chips
Color Temp.:	3000K/4100K/5500K/6000K
View Angle:	120 degree
Fixture Material:	Die-cast aluminum + Glass lens
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762), DLC (pending)
Test Reports:	LM79/LM80/IES available
Fixture info.:	16.9"L x 9.5"W x 13.6"H ,8.5kg