

Daylight Savings LLC Product List

Advantages:

- ◆ Mean Well UL/CUL driver
- ◆ High quality CREE chips
- ◆ Replacing 1,500W~2,000W MH/HPS
- ◆ 216° rotatable mounting bracket
- ◆ Multiple use, suitable for both indoors and outdoors: high bays, flood lights, spotlights, high pole, stadium lights etc
- ◆ Universal voltage: 100-277V/347V/480V
- ◆ High reflective rate of 92%
- ◆ Excellent heat sink with Copper heat pipe
- ◆ E-PTFE waterproof breathable membrane

Outdoor/indoor LED high bay/Flood Lights - RE.1,500W~2,000W (UL/CUL: E352762, DLC)

All models are UL CUL approved, the cert. number is E352762



DLC liste Model No. as below:

100-277V		347-480V	
DL-FLHB19-WW-50/90	750W,100-277V,3000K,90°x50°	DL-FLHB19-HV-WW-50/90	750W,347-480V,3000K,90°x50°
DL-FLHB19-WW35-50/90	750W,100-277V,3500K,90°x50°	DL-FLHB19-HV-WW35-50/90	750W,347-480V,3500K,90°x50°
DL-FLHB19-PW-50/90	750W,100-277V,4100K,90°x50°	DL-FLHB19-HV-PW-50/90	750W,347-480V,4100K,90°x50°
DL-FLHB19-PW45-50/90	750W,100-277V,4500K,90°x50°	DL-FLHB19-HV-PW45-50/90	750W,347-480V,4500K,90°x50°
DL-FLHB19-CW50-50/90	750W,100-277V,5000K,90°x50°	DL-FLHB19-HV-CW50-50/90	750W,347-480V,5000K,90°x50°
DL-FLHB19-CW-50/90	750W,100-277V,5500K,90°x50°	DL-FLHB19-HV-CW-50/90	750W,347-480V,5500K,90°x50°
DL-FLHB20-WW-50/90	950W,100-277V,3000K,90°x50°	DL-FLHB20-HV-WW-50/90	950W,347-480V,3000K,90°x50°
DL-FLHB20-WW35-50/90	950W,100-277V,3500K,90°x50°	DL-FLHB20-HV-WW35-50/90	950W,347-480V,3500K,90°x50°
DL-FLHB20-PW-50/90	950W,100-277V,4100K,90°x50°	DL-FLHB20-HV-PW-50/90	950W,347-480V,4100K,90°x50°
DL-FLHB20-PW45-50/90	950W,100-277V,4500K,90°x50°	DL-FLHB20-HV-PW45-50/90	950W,347-480V,4500K,90°x50°
DL-FLHB20-CW50-50/90	950W,100-277V,5000K,90°x50°	DL-FLHB20-HV-CW50-50/90	950W,347-480V,5000K,90°x50°
DL-FLHB20-CW-50/90	950W,100-277V,5500K,90°x50°	DL-FLHB20-HV-CW-50/90	950W,347-480V,5500K,90°x50°

ALL IS DLC & UL CUL LISTED

750W replace 1,500W MH/HPS
 950W replace 2,000W MH/HPS





750W



Spec.

Model No.	DL-FLHB19 (For 1,500W MH/HPS)
Input Voltage:	AC100-277V (50~60Hz)
Input Power:	LED: 730W Total: 750W
Luminous Flux:	70,200 LM
LED Source:	High power CREE LEDs
Color Temp.:	3000K /4100K/5500K /6000K
View Angle:	90°x11°, or 90°x50°(DLC)
Fixture Material:	Die-cast aluminum+Copper Pipe+Glass
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762), DLC listed
Testings:	LM79/LM80/IES available
Fixture info.:	20.3" (L)*17.2"(W)*15.5"(H), 22 kg



DLC Model No.:	
DL-FLHB19-WW-50/90	DL-FLHB19-WW35-50/90
DL-FLHB19-PW-50/90	DL-FLHB19-PW45-50/90
DL-FLHB19-CW50-50/90	DL-FLHB19-CW-50/90

Spec.

Model No.	DL-FLHB19-HV(For 1,500W MH/HPS)
Input Voltage:	AC 347-480V (50~60Hz)
Input Power:	LED: 730W Total: 750W
Luminous Flux:	70,200 LM
LED Source:	High power CREE LEDs
Color Temp.:	3000K /4100K/5500k /6000K
View Angle:	90°x11°, or 90°x50°(DLC)
Fixture Material:	Die-cast aluminum+Copper Pipe+Glas
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762), DLC listed
Testings:	LM79/LM80/IES available
Fixture info.:	20.3" (L)*17.2"(W)*15.5"(H), 22.5 kg

750W



DLC Model No.:	
DL-FLHB19-HV-WW-50/90	DL-FLHB19-HV-WW35-50/90
DL-FLHB19-HV-PW-50/90	DL-FLHB19-HV-PW45-50/90
DL-FLHB19-HV-CW50-50/90	DL-FLHB19-HV-CW-50/90

950W



Spec.

Model No.	DL-FLHB20 (For 2,000W MH/HPS)
Input Voltage:	AC100-277V (50~60Hz)
Input Power:	LED: 950W Total: 970W
Luminous Flux:	90,500 LM
LED Source:	High power CREE LEDs
Color Temp.:	3000K /4100K/5500k /6000K
View Angle:	90°x11°, or 90°x50°(DLC)
Fixture Material:	Die-cast aluminum+Copper Pipe+Glass
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762), DLC listed
Testings:	LM79/LM80/IES available
Fixture info.:	20.3" (L)*17.2"(W)*15.5"(H), 22.8 kg

DLC Model No.:	
DL-FLHB20-WW-50/90	DL-FLHB20-WW35-50/90
DL-FLHB20-PW-50/90	DL-FLHB20-PW45-50/90
DL-FLHB20-CW50-50/90	DL-FLHB20-CW-50/90

Spec.

Model No.	DL-FLHB20-HV(For 2,000W MH/HPS)
Input Voltage:	AC 347-480V (50~60Hz)
Input Power:	LED: 950W Total: 970W
Luminous Flux:	90,500 LM
LED Source:	High power CREE LEDs
Color Temp.:	3000K /4100K/5500k /6000K
View Angle:	90°x11°, or 90°x50°(DLC)
Fixture Material:	Die-cast aluminum+Copper Pipe+Glas
Fixture Surface:	Powder coating appearance
IP Rating:	IP65
Warranty:	5 years
Certifications:	UL/cUL(E352762), DLC listed
Testings:	LM79/LM80/IES available
Fixture info.:	20.3" (L)*17.2"(W)*15.5"(H), 23.5 kg

950W



DLC Model No.:	
DL-FLHB20-HV-WW-50/90	DL-FLHB20-HV-WW35-50/90
DL-FLHB20-HV-PW-50/90	DL-FLHB20-HV-PW45-50/90
DL-FLHB20-HV-CW50-50/90	DL-FLHB20-HV-CW-50/90